

empackEmpack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571**PRODUCT: Emzone White Lithium Grease (G7) - 400g****CODE: P6-045007****SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Item Numbers..... P6-045007
 Product Identity..... Emzone White Lithium Grease (G7) - 400g
 Manufacturer..... Empack Spraytech Inc.
 98 Walker Drive
 Brampton
 Ontario
 Canada
 L6T 4H6
 905-792-6571
 24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.
 Recommended Use..... Lubricant.
 Chemical Family..... Organic.

SECTION 02: HAZARDS IDENTIFICATION

Label Elements:
 Signal Word..... WARNING.
 Hazard Classification:
 Physical Hazards..... Aerosols - Category 3. Gases Under Pressure - Liquefied Gas .
 Health Hazards..... Skin Irritation - Category 2.
 Environmental Hazards..... Acute Aquatic Hazard - Category 3. Chronic Aquatic Hazard - Category 3.
 Hazard Statement..... Pressurized container: may burst if heated. Contains gas under pressure; may explode if heated. Causes skin irritation. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

Precautionary Statements:
 Prevention..... Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash hand thoroughly after handling. Wear protective gloves. Avoid release to the environment.
 Response..... IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.
 Storage..... Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
 Disposal..... Dispose of contents/ container in accordance with local/regional/national/international regulations.
 Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
Isobutane	75-28-5	15-40
Heptane (includng isomers)	64742-49-0	5-10
Petroleum Distillates	8052-41-3	1-5
Ammonia Solution	7664-41-7	0.1-1

SECTION 04: FIRST AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
 Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
 Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
 Ingestion..... If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

PRODUCT: Emzone White Lithium Grease (G7) - 400g**CODE: P6-045007****SECTION 04: FIRST AID MEASURES**

Most important symptoms/effects, acute .. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct and delayed contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified Organic Compounds.

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General Fire Hazards..... Non Flammable aerosol, but contains flammable propellant.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, and Cleaning Up earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available	Not available
Heptane (including isomers)	1,600 mg/m3 (RCP-TWA)	Not available	Not available	Not available	Not available	Not available
Petroleum Distillates	100 ppm	Non disposable	500 ppm	Non disposable	Non disposable	Non disposable
Ammonia Solution	25 ppm	35 ppm	50 ppm	Not available	25 ppm	
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.					
Individual Protection Measures:						
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.					
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.					
Respiratory Protection.....	Use dust and mist respirator.					
Thermal Hazards.....	None Known.					
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.					

PRODUCT: Emzone White Lithium Grease (G7) - 400g

CODE: P6-045007

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form.....	Aerosol.
Physical Appearance.....	White.
Odor.....	N/A.
Odor Threshold (ppm).....	N/A.
pH.....	9.0 - 11.0.
Aerosol Flame Projection.....	N/A.
Aerosol Vapour Pressure (psig, 21°C).....	60-80.
Evaporation Rate (n-Butyl Acetate = 1).....	N/A.
Vapour Density (Air=1).....	>1.
Melting/Freezing Point (°C).....	N/A.
Boiling Point liquid (°C).....	93-123°C .
VOC Content.....	Not available.
Specific Gravity (Liquid).....	0.900-0.960.
Specific Gravity (Aerosol).....	0.833-0.881.
Coefficient of Water/Oil Distribution.....	N/A.
Auto Ignition Temperature (°C).....	462. (Propellant).
Flash Point (°C), Method.....	-83. (Propellant). Closed cup.
Flashback.....	N/A.
Lower Flammable Limit (% Vol).....	1.4. (Propellant).
Upper Flammable Limit (% Vol).....	8.3. (Propellant).
Solubility in water.....	Soluble.
Viscosity.....	N/A.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Product not reactive under normal conditions of use.
Chemical Stability.....	Material is stable under normal conditions.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Keep away from heat. Strong oxidizing agents.
Hazardous Decomposition Products.....	Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Isobutane	658 mg/L (Rat - 4hrs)	Not available
Heptane (including isomers)	>23.3 mg/L (Rat - 4hrs)	>5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)
Petroleum Distillates	>5.5 mg/L (Rat - 4 hrs)	>5,000 mg/kg (Oral - Rat); >3,000 mg/kg (Dermal - Rabbit)
Ammonia Solution	2,000 ppm; 1.39 mg/L (Rat- 4hrs)	350 mg/kg (Oral - Rat);
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	Yes.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	No.	
Routes of entry - Skin Absorption.....	Yes.	
Symptoms Related to the Physical,	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	
Chemical and Toxicological Characteristics	Harmful or fatal if swallowed. Irritating to the eyes,nose and throat. Skin contact may cause irritation.	
Acute Toxicity.....	Causes skin irritation.	
Skin Corrosion/Irritation.....	May irritate eyes.	
Serious Eye Damage/Eye Irritation.....	May cause sensitization by skin contact. Inhalation may cause respiratory tract irritation.	
Respiratory or Skin Sensitization.....	No data available to indicate product or any components present at greater than 0.1% are mutagenic.	
Germ Cell Mutagenicity.....	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
Carcinogenicity.....	Based on available data, the classification criteria are not met.	
Reproductive Toxicity.....	No data available .	
STOT - Single Exposure.....	No data available .	
STOT - Repeated Exposure.....	No data available .	
Aspiration Hazard.....	No data available .	
Chronic Effects.....	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Breathing high concentrations of vapor may cause anesthetic effects and serious health effects.	

PRODUCT: Emzone White Lithium Grease (G7) - 400g

CODE: P6-045007

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Heptanes including isomers (CAS#: 64742-49-0): Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30 mg/L, 72 hrs. Chronic Toxicity Daphnia magna: NOEC 0.17 mg/L 21 days.

Persistence and degradability The product itself has not been tested.

Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.2.

DOT (US-Road)..... UN1950, AEROSOLS, Class 2.2, LTD QTY, Consumer Commodity, ORM-D.

IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.2.

IATA (International- Air)..... UN1950, AEROSOLS, Class 2.2, LTD QTY.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... WHMIS Classification. A: Compressed gas. D2A: Material causing very toxic effect. D2B: Material causing other toxic Materials.

Canadian Environmental Protection Act ... (CEPA) All ingredients listed appear on the Domestic Substances List (DSL).

US Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory.

OSHA..... This product is considered hazardous under the Federal OSHA hazard communication standard.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. .

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs

Latest Revision MAY 29/2018